

Hand Dryers



Make the most of your washroom space with our great range of commercial hand dryers. From stainless steel to chrome and white metal to plastic our wide range will suit most washroom designs.

Our high-speed automatic hand dryers are perfect for any public or commercial washroom.



Bringing Air to Life.



| Model | Code | ٧ | W | W motor | A max | Lp dB(A) 1m |
|------------------------------|----------|-----|-------|------------|----------|----------------|
| VORT Super Dry UVB White | ALV70907 | 240 | 1650/ | 750 | 0.7 | 76 |
| VORT Super Dry UVB Silver | ALV70908 | 240 | 2050 | 750 | 8.7 | 76 |



VORTICE HAND DRYER

Super Dry UV B

ENERGY SAVING

Features

- · Cabinet moulded in self-extinguishing ABS
- Steel wall-mounting flange
- EC brushless motor with thermal overload protection and shaft turning in ball bearings
- Heating element ON/OFF: a switch on the left hand side can be turned off to save energy in warmer environments.
- Germicidal capability thanks to UV lamp
- Dryer stops immediately when hands are withdrawn.
- Protection against vandalism: automatic shutoff after 25 seconds of continuous operation.
- Protection against overheating, overload and short-circuit.
- Drip collection tank
- HEPA filter



Technical Data

| Model | Code | V | W | W motor | A max | Lp dB(A) 1m |
|--------------------|----------|-----|------|------------|----------|----------------|
| VORT Optimal Dry R | ALV19227 | 240 | 2000 | 65 | 9 | 61.4 |



VORTICE HAND DRYER

Optimal Dry-R

ELEGANT DESIGN AND VANDAL RESISTANT

- Front cover moulded in thermosetting impact-resistant plastic, white
- Wall-mounting flange incorporating warm air outlet grille of moulded plastic (PP)
- $\,$ EC motor with thermal overload cutout
- Heating element protected by 2 devices: thermal fuse and resettable thermal overload limiter
- Air flow 170m³/h
- Dryer operated automatically by an infrared device with activation distance of up to 35 cm
- Dust filter
- IMQ safety certification



| Model | Code | Dimensions (mm) |
|-------------|---------|-----------------------|
| ALVHD2400PA | ALV1007 | H 248 x W 284 x D 202 |



Technical Data

| Model | Code | Dimensions (mm) |
|------------|---------|-----------------------|
| ALVHD1800W | ALV1001 | H 220 x W 248 x D 170 |





HD2400PA HIGH AIR FLOW

Features

- · Casing: 2.0mm thick, porcelain enamel coated steel
- · Nozzle: Chrome plated zinc
- Brush motor: 2400W, 5500rpm
- Designed with 105°C thermostat
- Heater assembly: Designed with 65°C thermostat
- Air flow rate 345 m³/h (202 CFM)
- Sound level: 70 ± 3 db
- Approximately 20–25 seconds drying time
- Adjustable sensitive distance of sensor from 10 to 30cm
- Power cut-off automatically in case of irregular use over 120 seconds
- 2 vandal proof lock screws and key wrench
- 5 year manufacturer's warranty



HAND DRYER

HD1800W

ECONOMICAL

- · Two year guarantee
- · Die-cast white metal cover for strength and durability
- · Superior technical design dual thermal overload protection on motor and heating element
- Certification of Compliance to foremost international safety standards and performance standards
- 'No touch' operation by electronic infra-red sensor maximises hygiene and economy of operation
- Fully automatic operation switches off within 3 seconds of hand removal – infra-red sensor
- Power rating: heating element 1700W
- 100w brushless motor (3450 rpm)
- Sound level: 63 +/- 3dB



| Model | Code | Dimensions (mm) |
|-----------------------------------|---------|-----------------------|
| ALVHD2200W - Die cast white metal | ALV1002 | H 210 x W 320 x D 175 |



HD2200W STYLISH AND ROBUST



Features

- Two year guarantee
- Choose from die-cast white metal cover or polished chrome plated die-cast aluminium cover for strength and durability even in high corrosion environments such as swimming pools
- Superior technical design dual thermal overload protection on motor and heating element
- Certification of Compliance to foremost international safety standards and performance standards
- 'No touch' operation by electronic infra-red sensor maximises hygiene and economy of operation
- Fully automatic operation switches off within 3 seconds of hand removal infra-red sensor
- · Power rating: heating element 2100W
- 100W induction motor



Technical Data

| Model | Code | Dimensions (mm) | Finish |
|-----------|---------|-----------------------|-----------------------|
| ALVHD2001 | ALV1003 | H 301 x W 230 x D 189 | Satin stainless steel |



HAND DRYER

HD2001
VELOCITY HIGH SPEED

- Two year guarantee
- · Auto resetting thermostat
- 1600W dryer
- 700W motor
- 900W heating element
- · Automatic infrared sensor
- Adjustable air speed: 75–100m/second
- Dries hands in less than 10 seconds
- Auto shut off in 60 seconds
- Air output to 100m/second
- Low energy usage reduces power consumption by up to 70%



| Model | Code | Dimensions (mm) | dBA | Finish | |
|-----------|---------|-----------------------|-----|-----------------------|--|
| ALVHD2002 | ALV1004 | H 230 x W 246 x D 145 | 75 | Satin stainless steel | |





HD2002

STYLISH AND ENERGY EFFICIENT

Features

- · Two year guarantee
- Quality 304 Grade stainless steel body
- Operating power of only 1000W (500W heating element) saving 80% of user's energy costs
- Smallest dryer in the range less than half the size of equivalent high speed dryers
- Infrared, self adjusting sensor: 51mm-254mm range
- Dryer delivers 101.7m³/hour (90m/s) This dries hands in 10-15 seconds, reducing CO_2 emissions.
- 29,000 rpm brush motor
- 55°C air output temperature



Technical Data

| Model | Code | Dimensions (mm) | Finish | |
|--|---------|----------------------|-----------------------|--|
| ALVHD2006 | ALV1005 | H 513 x W 250 x D 62 | Satin stainless steel | |
| Recess dimensions: H 495mm x W 235mm x D 122mm | | | | |




HAND DRYER


HD2006 **VELOCITY SEMI-RECESSED**

- Two year guarantee
- Auto resetting thermostat
- 1600W dryer
- 350–700W motor (adjustable)
- 450-900W heating element (adjustable)
- Automatic infrared, self-adjusting sensor: 51mm-330mm
- Dries hands in less than 10 seconds
- Auto shut off in 60 seconds
- Air output at 75–100m, self-adjusting
- Low energy usage reduces power consumption by up to 70%
- Available in polished stainless steel on request


VORTICE SUPER DRY UV B




VORTICE OPTIMAL DRY-R




HD2400PA




HD1800W




HD2200W




HD2001



HD2002



HD2006





Bringing Air to Life.

62 Enterprise Drive BERESFIELD NSW 2322 Info Hotline: 1300 883 544 www.allvent.com.au